

**INSTRUMENT APPROACH  
CHART (IAC)**

**PORTO VELHO / Gov. Jorge Teixeira de Oliveira, INTL (SBPV)**

**AD ELEV: 295'**

**RNAV (GNSS) X RWY 19**



D-ATIS	APP PORTO VELHO 120.25 120.80		TWR PORTO VELHO 118.20 121.50		GNDC NIL
N/A	FINAL CRS 190°	FAF 1930'	LNAV/VNAV DA / (OCH): 599' / (312')		LNAV MDA / (OCH): 690' / (410')

APCH Perdida: Subir para **3000'** no rumo **190** para espera em PV381.

Missed APCH: Climb to **3000'** on course **190** for holding over PV381.

RMK: 1) Para sistemas não compensados Baro-VNAV, LNAV/VNAV NAO AUTORIZADO abaixo de 0°C ou acima de 50°C.

1) For uncompensated systems Baro-VNAV, LNAV/VNAV NOT AUTHORIZED below 0°C or above 50°C.



DETOK	4.0	3.0	2.0	1.1	RWY19	KT	090	110	130	150	170	190
1930	1611	1292	974	690	ALT	FPM	500	600	700	800	900	1000
1643	1324	1005	687	410	(HGT)	FAF-MAPT	NA					

STRAIGHT-IN	CAT	A	B	C	D	E	
	DA / (OCH)	599' / (312')					NA
LNAV/VNAV	ALS/NO ALS/ RVR ALS (m)	NIL / 1400 / NIL					
	MDA / (OCH)	690' / (410')					
LNAV	ALS/NO ALS/ RVR ALS (m)	NIL / 1600 / NIL			NIL / 1900 / NIL		
	MDA / (OCH)	NA					
CIRCLING	VIS (m)	NA					

CHANGES: NEW CHART.