



CODING TABLE

This table supplements information contained in the chart to which it is associated. In spite of the fact the classification of waypoints (fly-by / flyover), courses, distances, altitudes, level and speed restrictions are mandatory, the providers may use the information as they find appropriate in order to code procedures. In other words, in case any particular coding is applied, it is mandatory for it to reflect the procedure published in the chart.

Identification	Aerodrome	Chart Code	AIRAC AMDT
IAC RNAV (GNSS) RWY 29	PORTO ALEGRE / Salgado Filho, INTL (SBPA))	SBPA_IAC_01J	12 OCT 17

Seq Num	IAP Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Phase	Path and Terminator	Course Angle	Turn	Upper Limit Altitude	Lower Limit Altitude	Speed Limit	Speed Limit Description	TM DST	VA	Role Of TheFix	Navigation Specification
10	Approach		N/A	PA023	A	IF	N/A	N/A	N/A	+4000.00	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	Approach	N	N/A	PA024	A	TF	358.27° Mag 341.29° True	N/A	N/A	+2300.00	N/A	N/A	6.00	N/A	IF	RNP APCH
10	Approach		N/A	PA006	A	IF	N/A	N/A	N/A	+4000.00	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	Approach	N	N/A	PA024	A	TF	288.26° Mag 271.28° True	N/A	N/A	+2300.00	N/A	N/A	5.00	N/A	IF	RNP APCH
10	Approach		N/A	KOTUB	A	IF	N/A	N/A	N/A	+4000.00	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	Approach	N	N/A	PA024	A	TF	218.31° Mag 201.33° True	N/A	N/A	+2300.00	N/A	N/A	6.00	N/A	IF	RNP APCH

10	Final		N/A	PA024	-	IF	N/A	N/A	N/A	+2300.00	N/A	N/A	N/A	N/A	IF	RNP APCH
20	Final	N	N/A	NETPI	-	TF	288.20° Mag 271.28° True	N/A	N/A	R1650.00	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	Final	N	N/A	SDF	-	TF	288.14° Mag 271.25° True	N/A	N/A	+790.00	N/A	N/A	2.70	-3.00	SDF	RNP APCH
40	Final	Y	N/A	RWY29	-	TF	288.13° Mag 271.27° True	N/A	N/A	+61.00	N/A	N/A	2.30	-3.00	LTP/FTP	RNP APCH
10	Missed	N	N/A	N/A	Z	CA	288.11° Mag 271.44° True	N/A	N/A	+3000.00	230.00	-	N/A	N/A	-230	RNP APCH
20	Missed	N	N/A	DAKAT	Z	DF	N/A	L	N/A	+4000.00	230.00	-	N/A	N/A	-230	RNP APCH
30	Missed	Y	N/A	DAKAT	Z	HM	107.96° Mag 91.30° True	R	N/A	+4000.00	230.00	-	N/A	N/A	-230	RNP APCH

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
PA023	S 30:05:36.60W 50:55:49.80
PA024	S 29:59:54.60W 50:58:03.00
PA006	S 30:00:01.20W 50:52:17.40
KOTUB	S 29:54:18.60W 50:55:32.40
DAKAT	S 30:05:01.80W 51:25:00.60
NETPI	S 29:59:48.00W 51:03:48.60
SDF	S 29:59:44.50W 51:06:54.91
RWY29	S 29:59:41.46W 51:09:33.80

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT