



CODING TABLE

IAC ILS Y RWY14					FLORIANÓPOLIS / Hercílio Luz, INTL (SBFL)							SBFL_IAC_00P		12 OCT 17	
Seq Num	IAP Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role Of TheFix	Navigation Specification
10	APPCH	N/A	N/A	MUKAL	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APPCH	N	N/A	ISASI	TF	140.69° Mag 121.46° True	N/A	N/A	+2800	N/A	N/A	6.01	N/A	IF	RNP APCH
10	APPCH	N/A	N/A	DIMOG	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APPCH	N	N/A	ISASI	TF	230.42° Mag 211.19° True	N/A	N/A	+2800	N/A	N/A	6.03	N/A	IF	RNP APCH
10	APPCH	N/A	N/A	ILRUK	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APPCH	N	N/A	ISASI	TF	50.42° Mag 31.19° True	N/A	N/A	+2800	N/A	N/A	5.97	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	ISASI	IF	N/A	N/A	N/A	+2800	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	IBDOD	TF	140.32° Mag 121.06° True	N/A	N/A	+2200	N/A	N/A	2.50	N/A	SDF	RNP APCH
30	FINAL	N	LOC/DME IFL	ESKEG	TF	140.31° Mag 121.05° True	N/A	N/A	+2000	N/A	N/A	1.50	N/A	FAF	RNP APCH
40	FINAL	Y	LOC/DME IFL	RWY14*	CF	140.31° Mag 121.01° True	N/A	N/A	@76	N/A	N/A	6.00	-3.03	LTP/FTP	N/A
10	MA	N	N/A	ESMUB	TF	140.28° Mag 120.88° True	N/A	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
20	MA	Y	N/A	ESMUB	HM	320.28° Mag 300.88° True	R	N/A	+4000	N/A	N/A	1.00 min	0.00	MAHF	RNP APCH

*Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
MUKAL	S 27:31:37.38W 48:48:29.26
ILRUK	S 27:39:53.67W 48:46:11.97
DIMOG	S 27:29:36.03W 48:39:12.38
ISASI	S 27:34:46.34W 48:42:42.99
IBDOD	S 27:36:03.97W 48:40:18.40
ESKEG	S 27:36:50.53W 48:38:51.61
RWY14	S 27:39:56.63W 48:33:04.27
ESMUB	S 27:48:49.96W 48:16:24.48

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT